

Performance P165V15



2-way kit

- Acoustically transparent dust cap
Better reproduction of mid frequencies
- Polyglass cone
Neutral sound without coloration
- Butyl surround
Promoting long life

- Aluminum basket
Easy mounting, strong rigid basket
- 25 mm [1"] Kapton®, voice-coil former
High power handling
- Voice-coil cooling system
Reliability, better sound quality

- Polypropylene capacitor
Natural reproduction of high frequencies
- 6/12dB/octave crossover
Optimized woofer and tweeter integration
- Adjustable tweeter level
For a better adaptation of level/
placement in vehicle

- "Diamond cutting"
aluminum protection cover
Better esthetic



- Aluminum/magnesium inverted dome tweeter
Optimized match between woofer and tweeter, non directive
- Double push-pull Neodymium magnet
Very linear tweeter
- Aluminum voice-coil former
Excellent heat dissipation characteristics

IT MAKES THE DIFFERENCE

- An outstanding musicality in this price level
- All Focal technologies from the beginning of the range

TECHNICAL CHARACTERISTICS

Woofer : 165 mm [6 1/2"]
Voice-coil : 25 mm [1"]
Magnet : 85 mm [3 5/16"]
Tweeter : 45 mm [1 3/4"]

Aluminum/magnesium inverted dome
Separate crossover : 2-way 6/12 dB/oct [4.5 kHz]
Adjustable tweeter level : 0 – 3 – 6 dB/oct
Max. power : 140W
Nom. power : 70W

Sensitivity (2,8 V/1m) : 93 dB
Frequency response : 60 Hz – 28 kHz
Accessories : Grilles supplied