

DLS SCANDINAVIA 3 COMPETITION GRADE MIDRANGE

DLS Scandinavia 3 is a midrange specially designed for competition use. The extreme audio performance makes it a winner in every Pro installation.

FEATURES AND BENEFITS:

Extreme audio performance, transparent and clear sound

> Great imaging and staging capabilities

Size of midrange 3"
Impedance 4 ohm

Rec. amp. power 50 - 200 Watt

Frequency range 80 Hz - 16 kHz (in axis) +- 3 dB

Fs / Qts / Vas 80 Hz / 0,54 / 1,3 litres

Sensitivity 84 dB

Cone material Kevlar ®*

Outer size 84 x 84 mm (3,31" x 3,31")

Mounting hole 78 mm (3,25")
Installation depth 45 mm (1.77")

Rec. X-over freq. LP: 200 Hz / HP: 6 kHz
Rec. enclosure 1 litre (0,035 ft³) or open air

Rec. cable DLS HQS 2 x 2,5


Rec. line cable DLS HQL

*Kevlar is a registered trade mark of duPont

DLS Svenska AB Göteborg - Sweden Phone: +46 31 840060 www.dls.se



DLS SCANDINAVIA 3 IMPEDANCE CURVE



DLS SCANDINAVIA 3

