

# Integration 165 VRS



## 2-way kit

- Butyl surround

Promoting long life

- Shallow mounting ( $2\frac{3}{16}$ " / 56mm)

Easy integration in the most exiguous spaces

- Polyglass cone

Neutral sound without coloration



- Zamak basket

Strong rigid chassis, non magnetic, non resonant

- $1\frac{1}{4}$ " (32mm) voice coil on Kapton® former

High power handling

- N38 neodymium magnet

High magnetic field for a high sensitivity

- Air core inductors with a low serial resistance

Inensitive to parasites, better sensitivity

- Adjustable tweeter level

Tweeter level setting according to the positioning

- Polypropylene/Aluminum capacitor

Natural reproduction of high frequencies

- Aluminum/magnesium inverted dome TNB tweeter

Smooth and detailed treble, large and precise sound stage

- Dual push-pull neodymium magnet

Excellent linearity of the tweeter

- Voice coil on aluminum former

High dissipation characteristics

## ADVANTAGES

- Easy installation for all kind of vehicles (shallow mounting:  $2\frac{3}{16}$ " / 56mm)
- Hi-Fi sound for an optimized realism
- Large and precise sound stage
- The essentials of Focal sound

## TECHNICAL CHARACTERISTICS

**Woofer:**  $6\frac{1}{2}$ " (165mm)

**Voice-coil:**  $1\frac{1}{4}$ " (32mm)

**Neodymium magnet:** N38

**TNB tweeter:**  $1\frac{3}{4}$ " (45mm)

**Aluminum/magnesium inverted dome tweeter**

**2-way component crossover:** 12/18dB/oct. [4.9kHz]

**Adjustable tweeter level:** [0, -3, -6dB]

**Max. power:** 120W

**Nom. power:** 60W rms

**Sensitivity (2.83V/1m):** 93dB

**Frequency response:** 70Hz – 28kHz

**Accessories:** supplied grilles